



INTERNAL Concrete Infill Recessed Covers



3104C-SLK



D3104B



R2-T450P-SLK

Rubber Seal & Locked


Standard Sizes

Code	Clear Opening (mm)	Frame Depth (mm)	Description	Loading (GLVW)*
D3104A	300 x 300	58	Galvanised Steel Cover & Frame, Double Rubber Sealed & Locked	10 Tonne
D3104B	450 x 450	58	Galvanised Steel Cover & Frame, Double Rubber Sealed & Locked	10 Tonne
D3104C	600 x 450	58	Galvanised Steel Cover & Frame, Double Rubber Sealed & Locked	10 Tonne
D3104D	600 x 600	58	Galvanised Steel Cover & Frame, Double Rubber Sealed & Locked	10 Tonne
D3104E	750 x 600	58	Galvanised Steel Cover & Frame, Double Rubber Sealed & Locked	10 Tonne
D3104F	750 x 750	58	Galvanised Steel Cover & Frame, Double Rubber Sealed & Locked	10 Tonne
D3104G	900 x 600	58	Galvanised Steel Cover & Frame, Double Rubber Sealed & Locked	10 Tonne
D3104H	900 x 750	58	Galvanised Steel Cover & Frame, Double Rubber Sealed & Locked	10 Tonne
R2-T450	Ø450	58	Galvanised Steel Cover & Frame, SQ to Round, Double Rubber Sealed	10 Tonne
R2-T450P-SLK	Ø450	56	Galvanised Steel Cover & Polyprop Frame, SQ to Round, SLK	10 Tonne
3104B-SLK	450 x 450	56	Galvanised Steel Cover & Polyprop Frame, SLK Lifting Keys	10 Tonne
3104C-SLK	600 x 450	56	Galvanised Steel Cover & Polyprop Frame, SLK Lifting Keys	10 Tonne
3104D-SLK	600 x 600	56	Galvanised Steel Cover & Polyprop Frame, SLK Lifting Keys	10 Tonne

*Must be infilled with C25 concrete to achieve full loading

SLK Lifting Keys

Covers which are infilled with concrete or block paving are notoriously heavy - the SLK heavy duty keys make lid removal considerably safer. The SLK keys have been tested and are capable of taking up to 600kg in force. UK Patent GB 2450631



Brass or Stainless Steel Edging

Brass or Stainless Steel Decorative edging is available on the D3104A-G.