

Date: 09 June 2010

Information Sheet No.: TDS00349

SEALOCRETE STABILISING SOLUTION AN ACRYLIC PRIMER FOR DECORATING

Sealocrete Stabilising Solution is a clear, ready to use water based treatment for bonding and priming porous surfaces prior to painting. Before using this product refer to the relevant Health & Safety Data Sheet.

Features

- Safe and easy to use, ready to use polymer emulsion, can be applied by brush, roller or spray.
- Versatile as can be used on many different substrates.

Uses

- Recommended for use as a pre-treatment for surfaces which are old, perished, chalky or porous.
- For use on concrete, plaster, plasterboard, cement renders, pebbledash etc.
- Once treated, the surface can be overpainted using conventional paints and varnishes.

Product Characteristics

Colour Milky.

Form Thin liquid.

Composition Acrylic emulsion.

Product Code 188075 5 Litre x 4

Shelf life/storage 12 months when stored in the original unopened containers. Store in dry conditions between 5°C and 25°C.

Typical Performance Data (approx.)

Coverage Typically 6m² per litre, depending on substrate porosity and texture.

Directions for use

IMPORTANT

Before using Sealocrete Stabilising Solution refer to the relevant Health & Safety Data Sheet. Available at www.sealocrete.com named as the code above.

Preparation

1. Any algae or mould must first be removed by mechanical means and/or with a Fungicidal Wash.
2. Surfaces must also be cleaned to remove any loose, friable or flaking material.

Application

1. The product must not be diluted, simply stir well.
2. Apply by brush, airless spray or roller direct from the container.
3. A second application may be necessary with surfaces which are particularly porous or powdery.
4. Allow surface to dry for up to 12 hours between coats or before decorating.

Cleaning

1. Clean equipment with soap and water immediately after use.
1. All splashes must be cleaned immediately with water containing household detergent.

Precautions in Use

Sealocrete Stabilising Solution can be applied to damp substrates. Do not apply Sealocrete Stabilising Solution when the temperature is below 5°C or when rain or frost is imminent.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Sealocrete Stabilising Solution.

Date: 09 June 2010

Information Sheet No.: TDS00349

Sales & Technical contacts at Bostik	Telephone	Facsimile	Email addresses
Sales	0844 371 1192	01785 241818	customer.service@bostik.com
Technical advice	0844 371 1197	01785 272867	technical.service@bostik.com
Technical Data & COSHH (MSDS) sheets	01785 272625	01785 212962	stafford.gatehouse@bostik.com

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.